ELECTRIC WINCH



Since 1950
THE SMALL
WINCH THAT
WORKS HARD

VULCAN'S SERIES 1 WINCH, BOTH COMPACT AND VERSATILE:

Made in Canada

2-year warranty

Meets and exceeds ASME B30.7 standard

Custom manufacturing

Testing and inspection certificate included



PERFECTLY SUITED FOR APPLICATIONS FROM THE MINING, FOREST PRODUCTS, WIND, MARINE, HYDROLECTRIC, METAL AND CONSTRUCTION INDUSTRIES, AS WELL AS FOR MUNICIPALITIES.

BRONZE ALLOY worm gear transmission

DIRECT TRANSMISSION a silent feature that eliminates the need for a conventional drive belt

AERONAUTICS-GRADE STEEL

CABLE with unparalleled performance and durability of the cable


COMPACT, STURDY DESIGN


for severe industrial applications

IN HOISTING MODE, the automatic electromagnetic break ensures a safe handling of the trolley

MOUNTING on the ground or vertical for better versatility

CORROSION AND WEATHER-PROOF PAINT





| MODEL | STD wire rope dia. | Motor | Weight | Layers specific parameters | Layer 1 | Layer 2 | Layer 3 | Layer 4 |
|--------|--------------------|-------|--------|-------------------------------|---------|---------|---------|---------|
| | in | hp | lb | | Layeri | Layer 2 | Layers | Layer 4 |
| WIU-30 | 1/8 | 3/4 | 100 | WLL hauling (lb) | 370 | 340 | 310 | 280 |
| | | | | WLL lifting (lb) | 370 | 340 | 310 | 280 |
| | | | | Layer wire rope capacity (ft) | 40 | 80 | 130 | 180 |
| | | | | Total wire rope capacity (ft) | 430 | | | |
| | | | | Line speed (ft/min) | 19 | 20.5 | 22.5 | 24.5 |

¹Total cable capacity is based upon cable diameter shown. Total cable capacity can vary depending on cable diameter chosen.