

VERTICAL LIFTING CLAMP WITH REMOTE CONTROL (SVC-L)

TWO YEAR WARRANTY

TECHNICAL SHEET

Vertical lifting clamp for vertical lifting of steel plates and steel structures

- With the use of a remote control lever and rope, (supplied with the clamp), the cam can be unlocked remotely to release the work piece.
- The spring-loaded tightening lock mechanism assures a positive initial clamping force.
- The clamping force increases in proportion to the weight of the load.
- The main body and the shackle are made of die-forging which is optimally tempered for maximum strength and durability.
- High-frequency quenching of special alloy steels gives greater durability to the cam.
- The main body is a baked-on finished.

TECHNICAL SPECS

MODEL	Capacity (Tons)	Jaw opening (mm)	Weight (kg)
SVC0.5L	0,5	0~19	3
SVC1L	1	0~25	6
SVC2L	2	0~30	10,5
SVC3L	3	0~35	12,5

Capacity	H h1	h2	h3	B	b1	h2	D1	D2	T1*	T2
Compositor					Dimensio	ons (mm	J			
				'		_				
SVC3L	3	0-	-35	1	2,5					
SVC2L	2	0-	-30	1	0,5					
SVC1L	1	0-	-25		6					
SVC0.5L	0,5	0-	0~19		3					

Conscitu	Dimensions (mm)													
Capacity	L	Н	h1	h2	h3	В	b1	b2	D1	D2	T1*	T2	T3	t
0,5	250	158	80	60	36	131	36	26	36	64	89(80)	67	49	12
1	310	185	90	69	45	151	42	32	48	85	113(104)	81	59	16
2	375	210	100	77	47	172	48	39	60	106	130(118)	97	71	18
3	405	225	105	81	47	182	51	42	66	117	141(129)	102	75	20

^{*}Refer to values in parenthesis when remote control lever not installed.

EXAMPLES OF USE







